

PTC-10T Model:

> 10.1" HMI Touch Panel PC with 3mm Tempered Glass, WiFi and RS-232 **Ports**





Main Feature

- 10.1" 1280 x 800 with PCAP touch screen
- A64, Cortex-A53Processor
- Fanless cooling system and ultra low power consumption
- Front IP65 for protection against water and dust
- A true flat, easy to clean front surface with edge to edge design
- Meet standard VESA hole (100 x 100mm), support desk top stand / wall mount / swing arm mounting

Application:

Factory / Processor Automation, building automation, HMI, vending machine and interactive IoT applications

Specification		
Product Model	PTC-10T	
Processor	A64, Cortex-A53, Quad-core, 1.5GHz	
Memory	Onboard 2GB DDR3L	
Storage	Onboard 8GB eMMC	
Operating System	Android 6.0	

NORCO S.E.A. PTE LTD GST Registration No.: 200901437Z

Tel: (65) 6853 0809 20 Woodlands Link, #09-23, Woodlands East Ind' Estate, Singapore 738733

Fax: (65) 6853 0153

Company Registration No.: 200901437Z

All specifications are subject to change without prior notice



Display	Display Type: 10.1" <u>LED Panel</u> Resolution: 1280 × 800 Luminance: 300 nit View Angel: 170°(H), 170°(V)
LAN	1 x 10/100M Ethernet, WIfi, Bluetooth, 3G/4G (optional)
Back panel I/O port	1 x RJ45; 2 x USB 2.0; 1 x Micro USB (OTG); 1 x SD/TF card slot; 1 x HDMI; 1 x Audio out; 2 x COM; 1 x Power / Reset Switch; 1 x 12VDC input
Touch / Glass	Projected Capacitive Multi Touch Screen
Construction	Heavy duty steel and Aluminum front panel
Environment	Operating temperature: 0°C to 60°C Relative humidity: 10% to 90%non-condensing Vibration: 17 to 500HZ 1G PTP; Shock: 1G /peak(11m sec)
Compliance	CE; FCC; ROHS
Dimension W x H x D (mm)	216 x 185 x 56
Ordering Information	
PTC-10T	10.1" HMI Touch Panel PC, A64 Cortex-A53, with 100~240VAC to DC 12V adapter

Structure Diagram

